
Small Signal Schottky Diode





Features

- V_R 60V/50V/40V
- I_{FAV} 70mA

Mechanical Data

- **Package**: SOD323
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

	Marking
SD101AWS	S1
SD101BWS	S2
SD101CWS	S3

■Maximum RatingS (Ta=25°C Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	Conditions	VALUE	
Reverse voltage	V_R	V	I_R=10uA	SD101AWS	60
				SD101BWS	50
				SD101CWS	40
Average forward current	I_{FAV}	mA	T_c=25°C	70	
Repetitive Peak Forward Current	I_{FRM}	A	tp=1ms，δ=0.25	0.07	
Power dissipation	P_D	mW		200	
Maximum junction temperature	T_j	°C		-55 to +125	
Storage temperature range	T_{stg}	°C		-55 to +150	
Thermal Resistance Junction to Ambient Air	$R_{\theta JA}$	°C /W		500	

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	Conditions		VALUE	
Maximum Forward voltage	VF	V	I_F=1mA, T_A=25°C		SD101AWS	0.41
					SD101BWS	0.4
					SD101CWS	0.39
	VF	V	I_F=15mA, T_A=25°C		1.0	
Maximum Reverse current	IR	uA	SD101AWS	V_R=50V,T_A=25°C	0.2	
			SD101BWS	V_R=40V,T_A=25°C		
			SD101CWS	V_R=30V,T_A=25°C		
Minimum Breakdown voltage	$V_{(BR)}$	V	I_R=10uA		SD101AWS	60
					SD101BWS	50
					SD101CWS	40
Maximum Junction capacitance	C_J	pF	V_R=1V, f =1MH$_Z$		2	

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SD101AWS Thru SD101CWS	F2	Approximate 0.0048	3000	30000	120000	7” reel

■ Characteristics (Typical)

Fig 1：P_D-Ta Curve




Fig 2：Capacitance Capability




Fig 3：Typical Forward Characteristics






Fig 4：Typical Reverse Characteristics




■ Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MN	MAX
A	---	0.0393	---	1.0000
A1	0.0000	0.0039	0.0000	0.1000
A2	0.0314	0.0354	0.8000	0.9000
b	0.0098	0.0157	0.2500	0.4000
c	0.0031	0.0059	0.0800	0.1500
D	0.0472	0.0551	1.2000	1.4000
E	0.0629	0.0709	1.6000	1.8000
E1	0.0984	0.1063	2.5000	2.7000
L	0.0187TYP		0.475TYP	
L1	0.0098	0.0157	0.250	0.400
θ	0°	8°	0°	8°

Note:
1. All dimensions are in millimeters (mm) unless otherwise specified.
[所有尺寸均以毫米为单位，除非另有说明]
2. General tolerances: ±0.10mm unless otherwise specified.
[通用公差为±0.10mm，除非另有说明]
3. Dimensions and tolerances per ASME Y14.5M-2018.
[尺寸和公差遵循 ASME Y14.5M-2018 标准]
4.All dimensions shown are exclusive of burrs and gate residues.
Burrs and gate vestiges shall not exceed 0.15 mm in maximum.
[所有尺寸均不包括毛刺和浇口残留。毛刺与浇口残留的尺寸最大不得超过 0.15mm]
5.Dimension b does not include dambar protrusion of max 0.100 mm per side.
[尺寸b不包括单边最大0.100 MM的中筋凸出部分]
6.Dimensions D and E are the overall extreme outer dimensions of the mold compound. These dimensions exclude mold flash, lead flash, protrusions and burrs but include the maximum allowable mold mismatch.
[D和E是塑封体的外部极限尺寸，不包括包封溢料、内引线溢料、凸出部分以及胶体毛刺，但是包含了包封错位的最大尺寸]
7.Formed leads shall be planar with respect to one another within a maximum of 0.076 mm relative to the seating plane.
[成型的管脚应为同一平面，共面性最大为0.1mm]

■ Soldering Footprint



Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.