

Dual PNP+PNP Digital Transistors (Built-in Resistors)





Features

- Moisture sensitivity level 1
- Halogen free and RoHS compliant
- Surface mount package ideally suited for automatic insertion

Application

- Signal amplification
- Switching circuit

Mechanical data

- **Package**: SOT-363S
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102

■ Maximum Ratings (T_a=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Value
Device marking code				B11
Collector-base voltage	V_{CC}	V		-50
Collector-emitter voltage	V_{IN}	V		-40 to +10
Collector current	I_O	mA		-100
Power dissipation	P_D	mW		150
Operation junction temperature	T_J	℃		-55 to +150
Storage temperature	T_{STG}	℃		-55 to +150

■ Electrical Characteristics (Ta=25℃ Unless otherwise specified)

Item	Symbol	Unit	Conditions	Min	Typ	Max
Input voltage	$VI_{(off)}$	V	V_{CC}=-5V,Ic=-100uA	-0.5		
	$VI_{(on)}$	V	V_O=-0.3V,Ic=-10mA			-3
Output voltage	$Vo_{(on)}$	V	Io /Ii =-10mA/-0.5 mA			-0.3
Input current	I_I	mA	V_I=-5V			-0.88
Output current	$I_{O(off)}$	uA	V_{CC}=-50V, Vi=0			-0.5
DC current gain	G_I		Vo=-5V, Io =-5mA	30		
Input resistance	R_1	kΩ		7	10	13
Resistance ratio	R_2/R_1			0.8	1	1.2
Transition frequency	f_T	MHz	V_O=-10V,I_O=-5mA,f=100MHz		250	

■ Thermal Characteristics

Parameter	Symbol	Unit	Value
Thermal resistance, junction-to-ambient	$R_{\theta J-A}$(1)	℃/W	834
Thermal resistance, junction-to-case	$R_{\theta J-C}$(1)	℃/W	667

Note:

（1）Device mounted on PCB, single-sided copper， with standard footprint

■Ordering Information

Prefered P/N	Packing code	Unit weight(g)	Minimum package(pcs)	Inner box quantity(pcs)	Outer carton quantity(pcs)	Delivery mode
UMB11NS	F2	Approximate 0.009	3000	30000	120000	7” reel
UMB11NS	F3	Approximate 0.009	10000	/	210000	7” reel

■Characteristics(Typical)

Fig 1：Input Voltage (On) Characteristics




Fig 2：Input Voltage (Off) Characteristic




Fig 3：DC Current Gain Characteristics




Fig 4：Output Voltage Characteristics







Fig 5：PD-Ta Curve





SYMBOL	MILLIMETER		
	MIN	NOM	MAX
E	0.15	0.25	0.35
B	1.15	1.25	1.35
C	2.00	2.10	2.20
P		0.650BSC	
A	1.80	2.00	2.20
T	0.00	0.05	0.100
D	0.90	0.95	1.00
L1	0.20	0.30	0.40
a		4°±4°	
M	0.10	0.15	0.25

■ **Suggested Pad Layout**



UNIT：mm

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.