
Digital Transistors (Built-in Resistors)




Features

- Epoxy meets UL-94 V-0 flammability rating
- Built-in bias resistors enable the configuration of an inverter circuit without connecting external input resistors
- Surface mount package ideally Suited for Automatic Insertion

Mechanical Data

- **Package:** SOT-363
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** D10

■Equivalent circuit



■Maximum Ratings (Ta=25℃ Unless otherwise specified）

DTR1-NPN

ITEM	SYMBOL	UNIT	CONDITIONS	VALUE
Supply Voltage	V_{CC}	V		50
Input Voltage	V_{IN}	V		-5 to +12
Output Current	I_O	mA		100
Power Dissipation	P_D	mW		150
Junction Temperature （Single）	Tj	℃		150
Storage Temperature	T_{STG}	℃		-55 to +150

DTR2-PNP

ITEM	SYMBOL	UNIT	CONDITIONS	VALUE
Supply Voltage	V_{CC}	V		-50
Input Voltage	V_{IN}	V		-12 to +5
Output Current	I_O	mA		-100
Power Dissipation	P_D	mW		150
Junction Temperature	Tj	℃		150
Storage Temperature	T_{STG}	℃		-55 to +150

■Electrical Characteristics (Ta=25℃ unless otherwise specified)

DTR1-NPN

ITEM	SYMBOL	UNIT	CONDITIONS	MIN	TYP	MAX
Input voltage	$VI_{(off)}$	V	V_{CC}=5V,Ic=100uA	0.5	-	-
	$VI_{(on)}$	V	V_O=0.3V,Ic=5mA	-	-	1.1
Output voltage	$Vo_{(on)}$	V	Io /Ii =5mA/0.25 mA	-	-	0.3
Input current	I_I	mA	V_I=5V	-	-	3.6
Output current	$I_{O(off)}$	uA	V_{CC}=50V, Vi=0	-	-	0.5
DC current gain	G_I		Vo=5V, Io =10mA	80	-	-
Input resistance	R_1	kΩ		1.54	2.2	2.86
Resistance ratio	R_2/R_1			17	21	26
Transition frequency	f_T	MHz	V_{CE}=10V,I_E=5mA,f=100MHz	-	250	-

DTR2-PNP

ITEM	SYMBOL	UNIT	CONDITIONS	MIN	TYP	MAX
Input voltage	$V_{I(off)}$	V	V_{CC}=-5V,Ic=-100uA	-0.5	-	-
	$V_{I(on)}$	V	V_O=-0.3V,Ic=-5mA	-	-	-1.1
Output voltage	$V_{O(on)}$	V	Io /Ii =-5mA/-0.25 mA	-	-	-0.3
Input current	I_I	mA	V_I=-5V	-	-	-3.6
Output current	$I_{O(off)}$	uA	V_{CC}=-50V, Vi=0	-	-	-0.5
DC current gain	G_I		Vo=-5V, Io =-10mA	80	-	-
Input resistance	R_1	kΩ		1.54	2.2	2.86
Resistance ratio	R_2/R_1			17	21	26
Transition frequency	f_T	MHz	V_{CE}=-10V,I_E=-5mA,f=100MHz	-	250	-

■ **Ordering Information** (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
UMD10N	F2	Approximate 0.009g	3000	30000	120000	7” reel

■ **Characteristics** (Typical)

Fig. 1 - DTR1 DC Current Gain Characteristics




Fig. 2 - DTR1 Input Voltage (on) Characteristics




Fig. 3 - DTR1 Input Voltage (off) Characteristics




Fig. 4 - DTR1 Output Voltage Characteristics




Fig. 5 - DTR2 DC Current Gain Characteristics




Fig. 6 - DTR2 Input Voltage (on) Characteristics




Fig. 7 - DTR2 Input Voltage (off) Characteristics







Fig. 8 - DTR2 Output Voltage Characteristics




■SOT-363 Package Outline Dimensions




DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.035	0.043	0.9	1.1
A1	0	0.004	0	0.1
A2	0.035	0.039	0.9	1
b	0.006	0.014	0.15	0.35
c	0.002	0.01	0.05	0.25
D	0.071	0.087	1.8	2.2
E	0.045	0.053	1.15	1.35
E1	0.085	0.096	2.15	2.45
e	0.026Typ		0.65Typ	
e1	0.047	0.055	1.2	1.4
L	0.021Typ		0.525Typ	
L1	0.01	0.018	0.26	0.46
θ	0°	8°	0°	8°





■SOT-363 Suggested Pad Layout



Unit：mm

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.