
## Bridge Rectifiers




### Features

- Glass passivated chip junction
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

### Typical Applications

General purpose use in AC/DC bridge full wave rectification for SMPS, lighting ballast, adapter, battery charger, home appliances, office equipment, and telecommunication applications.

### Mechanical Data

- **Package**: DB
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, Halogen free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

### ■Maximum Ratings (Ta=25℃ Unless otherwise specified）

| PARAMETER | SYMBOL | UNIT | DBL201 | DBL202 | DBL203 | DBL204 | DBL205 | DBL206 | DBL207 |
|---|---|---|---|---|---|---|---|---|---|
| Device marking code | | | DBL201 | DBL202 | DBL203 | DBL204 | DBL205 | DBL206 | DBL207 |
| Maximum Repetitive Peak Reverse Voltage | $V_{RRM}$ | V | 50 | 100 | 200 | 400 | 600 | 800 | 1000 |
| Maximum RMS Voltage | $V_{RMS}$ | V | 35 | 70 | 140 | 280 | 420 | 560 | 700 |
| Maximum DC blocking Voltage | $V_{DC}$ | V | 50 | 100 | 200 | 400 | 600 | 800 | 1000 |
| Average rectified output current @60Hz sine wave, R-load, Tc=118℃ | $I_O$ | A | 2.0 | | | | | | |
| Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃ | $I_{FSM}$ | A | 60 | | | | | | |
| Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃ | | | 120 | | | | | | |
| Current squared time @1ms≤t≤8.3ms Tj=25℃, Rating of per diode | $I^2t$ | $A^2s$ | 14.9 | | | | | | |
| Storage temperature | $T_{stg}$ | ℃ | -55 ~ +150 | | | | | | |
| Junction temperature | $T_j$ | ℃ | -55 ~ +150 | | | | | | |

### ■Electrical Characteristics（$T_a$=25℃ Unless otherwise specified）

| PARAMETER | SYMBOL | UNIT | TEST CONDITIONS | DBL201 | DBL202 | DBL203 | DBL204 | DBL205 | DBL206 | DBL207 |
|---|---|---|---|---|---|---|---|---|---|---|
| Maximum instantaneous forward voltage drop per diode | $V_F$ | V | $I_{FM}$=1.0A | 1.0 | | | | | | |
| Maximum DC reverse current at rated DC blocking voltage per diode | $I_R$ | μA | $T_j$=25℃ | 5 | | | | | | |
| | | | $T_j$=125℃ | 100 | | | | | | |
| Typical junction capacitance | Cj | pF | Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C | 19 | | | | | | |

## ■Thermal Characteristics （$T_a$=25℃ Unless otherwise specified）

| PARAMETER | SYMBOL | UNIT | DBL201 | DBL202 | DBL203 | DBL204 | DBL205 | DBL206 | DBL207 |
|---|---|---|---|---|---|---|---|---|---|
| Typical Thermal Resistance | RθJ-A | ℃/W | 40.0 | | | | | | |
| | RθJ-L | | 15.0 | | | | | | |
| | RθJ-C | | 8.0 | | | | | | |

Note: Device mounted on P.C.B with 35mm*25mm*1.7mm

## ■Ordering Information (Example)

| PREFERED P/N | PACKING CODE | UNIT WEIGHT(g) | MINIIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---|---|---|---|---|---|---|
| DBL201 ~ DBL207 | B1 | Approximate 0.37 | 50 | 2500 | 10000 | Tube |

## ■ Characteristics (Typical)

FIG1:Io-Tc Curve





FIG2:Surge Forward Current Capability





FIG3: Typical Forward Voltage







FIG4:Typical Reverse Characteristics



## ■ Outline Dimensions




| DBL | | |
|---|---|---|
| Dim | Min | Max |
| A | 6.20 | 6.50 |
| B | 7.60 | 8.90 |
| C | 5.00 | 5.20 |
| D | 8.13 | 8.51 |
| E | 0.46 | 0.58 |
| F | 2.35 | 2.45 |
| G | 0.22 | 0.33 |
| H | 3.81 | 4.69 |
| I | 1.39 | 1.90 |
| J | 1.27 | 2.03 |
| K | 0.89 | 1.14 |
| L | 7.24 | 8.00 |

## Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.