
Three Phase Bridge Rectifiers



Features

- Thin single in-line package
- Glass passivated chip junction
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for Server、Frequency converter、Industrial power supply.

Mechanical Data

- **Package**: 3GBJ
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25℃ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	DG15NA140	DG15NA160
Device marking code				DG15NA140	DG15NA160
Maximum Repetitive Peak Reverse Voltage		V_{RRM}	V	1400	1600
Maximum RMS Voltage		V_{RMS}	V	980	1120
Maximum DC blocking Voltage		V_{DC}	V	1400	1600
Average rectified output current @60Hz sine wave, R-load	With heatsink Tc =135℃	I_O	A	15.0	
	Without heatsink Ta =25℃			4.0	
Forward Surge Current (Non-repetitive) @8.3ms Half-sine wave,1 cycle, Tj=25℃		I_{FSM}	A	350	
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃				700	
Current squared time @1ms≤t≤8.3ms Tj=25℃, Rating of per diode		I^2t	A^2s	508	
Storage temperature		T_{stg}	℃	-55 ~ +150	
Junction temperature		T_j	℃	-55 ~ +150	
Dielectric strength @ Terminals to case, AC 1 minute		V_{dis}	KV	2.5	
Mounting torque @Recommend torque：5kg·cm		Tor	kg·cm	8	

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	DG15NA140	DG15NA160
Maximum instantaneous forward voltage drop per diode	V_F	V	I_{FM}=7.5A	1.0	
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j=25℃	5	
			T_j=125℃	500	
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	115	

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	DG15NA140	DG15NA160
Typical Thermal Resistance	Between junction and ambient, Without heatsink	RθJ-A	℃/W	18.0	
	Between junction and case, With heatsink	RθJ-C		0.5	

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
DG15NA140 ~ DG15NA160	A1	Approximate 10	100	100	1000	BOX
DG15NA140 ~ DG15NA160	B1	Approximate 10	10	/	1000	TUBE

■ Characteristics (Typical)

FIG1:Io-Tc Curve








FIG2:Surge Forward Current Capability







■ Outline Dimensions



3GBJ		
Dim	**Min**	**Max**
A	34.7	35.3
B	24.7	25.3
C	19.5	20.1
D	5.1	5.6
E	3.9	4.5
F	7.2	7.8
G	0.4	0.6
H	0.9	1.1
I	2.0	2.4
J	2.2	2.6
K	3.8	4.2
L	5.2	5.6
M	13.9	14.5
N	3.5	3.9
P	0.60	0.80
R1	2.7	3.7
R2	5.3	6.3
S	1.3	1.9
T	17.2	17.8

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.