

Plastic High Voltage Rectifier





Features

- VR 3KV
- IO 1.0A
- Glass passivated chip junction
- High surge current capability

Mechanical Data

- **Package**: SMA-W
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	EM530AG
Device marking code			EM530AG
Maximum Repetitive peak reverse voltage	V_{RRM}	V	3000
Maximum RMS Voltage	V_{RMS}	V	2100
Maximum DC Blocking Voltage	V_{DC}	V	3000
Average rectified output current @ 60Hz sine wave, Resistance load	I_O	A	1.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	30
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			60
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	3.73
Storage temperature	Tstg	℃	-55 ~ +150
Junction temperature	Tj	℃	-55 ~ +150

■Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	EM530AG
Maximum instantaneous forward voltage	V_F	V	I_{FM}=1.0A	2.5
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	Tj =25℃	5
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	2.3

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
EM530AG	F1	Approximate 0.067	5000	/	80000	Reel

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	EM530AG
Typical Thermal Resistance	$R_{\theta J-A}$	℃/W	80[1)]

■ Characteristics (Typical)

FIG.1: Io-Ta Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage






FIG.4: Typical Reverse Characteristics



■ Outline Dimensions



SMA-W		
Dim	Min	Max
A	4.00	4.60
B	2.40	2.65
C	4.80	5.31
D	2.05	2.45
E	0.80	1.50
F	0.10	0.20
G	1.15	1.80

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.