

Super Fast Recovery Rectifier Diode





Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Solder dip 260°C max. 10 s, per JESD 22-B106

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.

Mechanical Data

- **P**ackage: DO-214AB (SMC)

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Polarity: Color band denotes the cathode end

■Maximum Ratings (T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	ES5A	ES5B	ES5C	ES5D	ES5F	ES5G	ES5H	ES5J
Device marking code			ES5A	ES5B	ES5C	ES5D	ES5F	ES5G	ES5H	ES5J
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	150	200	300	400	500	600
Maximum RMS Voltage	V_{RMS}	V	35	70	105	140	210	280	350	420
Maximum DC blocking Voltage	V_{DC}	V	50	100	150	200	300	400	500	600
Average Rectified Output Current @60Hz sine wave, Resistance load, TL (FIG.1)	I_O	A	5.0							
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	150							
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			300							
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	94							
Storage Temperature	T_{stg}	℃	-55 ~ +150							
Junction Temperature	T_j	℃	-55 ~ +150							

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	ES5A	ES5B	ES5C	ES5D	ES5F	ES5G	ES5H	ES5J
Maximum instantaneous forward voltage	V_F	V	IFM=5.0A	0.95				1.3		1.7	
Maximum reverse recovery time	t_{rr}	ns	IF=0.5A,IR=1.0A, Irr=0.25A	35							
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	Tj =25℃	5							
			Tj =125℃	100							
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	75				37		35	

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	ES5A	ES5B	ES5C	ES5D	ES5F	ES5G	ES5H	ES5J
Typical Thermal Resistance	$R_{\theta J-A}$(1)	℃/W	50							
	$R_{\theta J-L}$(1)		15							
	$R_{\theta J-C}$(1)		12							

Note(1)
Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.6" x 0.6" (16 mm x 16 mm) copper pad areas

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
ES5A~ES5J	F1	Approximate 0.254	3000	/	42000	13” reel

■ Characteristics(Typical)

FIG.1: Io-TL Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage




FIG.4: Typical Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time




■ Outline Dimensions



DO-214AB (SMC)		
Dim	Min	Max
A	6.60	7.11
B	2.85	3.27
C	5.59	6.22
D	7.75	8.13
E	1.99	2.61
F	0.15	0.31
G	0.76	1.52
H	0.05	0.20

■ Suggested pad layout



DO-214AB (SMC)	
Dim	Min
P1	9.9
P2	3.84
Q1	3.03
Q2	3.82

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.