

Surface Mount Schottky Rectifier





Features

- ●Low profile package
- ● Ideal for automated placement
- ● Guardring for overvoltage protection
- ● Low power losses, high efficiency
- ● High forward surge capability
- ● Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.

Mechanical Date

- ● **Package**: SOD-323FL
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- ● **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- ● **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (Tj=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	FM22
Device marking code			**FM22**
Repetitive peak reverse voltage	V_{RRM}	V	20
Average rectified output current @60Hz sine wave, Resistance load, Tc (FIG.1)	I_O	A	2.0
Surge(non-repetitive)forward current @ 60Hz half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	30
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			60
Current squared time @1ms≤t≤8.3ms Tj =25℃， Rating of per diode	I2t	A2S	3.74
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	Cj	pF	72
Storage temperature	T_{stg}	℃	-55 ~+150
Junction temperature	Tj	℃	-55 ~+125

■Electrical Characteristics（T_j=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Peak Forward Voltage	V_{FM}	V	I_{FM}=2.0A Tj=25℃	-	0.49	0.55
			I_{FM}=2.0A Tj=100℃	-	-	0.50
Maximum DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	mA	V_{RM}=V_{RRM} Tj=25℃	-	-	0.2
	I_{RRM2}		V_{RM}=V_{RRM} Tj=100℃	-	-	10

■Thermal Characteristics （T_j=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	FM22
Thermal Resistance	RθJ-A	℃/W	90[1)]
	RθJ-c		46[1)]

Note：

(1) Thermal resistance between junction and ambient and between junction and lead mounted on P.C.B with 3mm*3mm copper pad areas.

■ Characteristics(Typical)

FIG1:Io-Tc Curve




FIG2：Surge Forward Current Capability




FIG.3: Forward Voltage






FIG.4: Instantaneous Reverse Characteristics




■ Outline Dimensions



SOD-323FL		
Dim	Min	Max
A	1.05	1.45
B	0.90	1.15
C	2.30	2.70
D	0.80	1.20
E	0.25	0.70
F	0.05	0.25

■ Suggested pad layout



SOD-323FL	
Dim	Millimeters
P1	1.30
Q1	1.00
Q2	1.50

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.