
FR201G THRU FR207G

Fast Recovery Rectifier



Features

- High efficiency
- High current capability
- High reliability
- High surge current capability
- Low power loss
- Glass passivated chip junction
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Mechanical Data

- **Package**: DO-204AC(DO-15)

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant

- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:**Color band denotes cathode end

■Maximum Ratings (Ta=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	FR201G	FR202G	FR203G	FR204G	FR205G	FR206G	FR207G
Device marking code			FR201G	FR202G	FR203G	FR204G	FR205G	FR206G	FR207G
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	50	100	200	400	600	800	1000
Average Forward Current @60Hz sine wave, Resistance load, Ta=75℃	$I_{F(AV)}$	A	2.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	60						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			120						
Current squared time @1ms≤t8.3≤ms Tj=25℃， Rating of per diode	I^2t	A^2s	15						
Typical junction capacitance @Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	Cj	pF	18				13	12	
Storage Temperature	T_{stg}	℃	-55 ~ +150						
Junction Temperature	Tj	℃	-55 ~ +150						

■Electrical Characteristics（Ta=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	FR201G	FR202G	FR203G	FR204G	FR205G	FR206G	FR207G
Maximum instantaneous forward voltage drop per diode	VF	V	I_{FM}=2.0A	1.3						
Maximum DC reverse current at rated DC blocking voltage per diode	IR	μA	T_j =25℃	2.5						
			T_j =125℃	100						
Maximum reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A, I_{rr}=0.25A	150				250	500	

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	FR201G	FR202G	FR203G	FR204G	FR205G	FR206G	FR207G
Typical Thermal Resistance	$R_{\theta J\text{-}A}$	℃/W	50						

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
FR201G~FR207G	D1	Approximate 0.38	3000	3000	30000	Tape
FR201G~FR207G	C1	Approximate 0.38	500	500	25000	Bulk

■ Characteristics (Typical)

FIG.1: Io-Ta Curve




FIG.2: Forward Surge Current Capability




FIG.3: Forward Voltage




FIG.4: Typical Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Outline Dimensions



DO-204AC(DO-15)		
Dim	Min	Max
A	5.80	7.60
B	2.60	3.60
C	25.4	/
D	0.70	0.90

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.