
Surface Mount General Purpose Rectifier




Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in general purpose rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.



Mechanical Data

- **Package**: SMAF
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (Ta=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	G3AF	G3BF	G3DF	G3GF	G3JF	G3KF	G3MF
Device marking code			G3AF	G3BF	G3DF	G3GF	G3JF	G3KF	G3MF
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	50	100	200	400	600	800	1000
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I_O	A	3.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	90						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			180						
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	33.6						
Storage temperature	T_{stg}	℃	-55 ~ +150						
Junction temperature	T_j	℃	-55 ~ +150						

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	G3AF	G3BF	G3DF	G3GF	G3JF	G3KF	G3MF
Maximum instantaneous forward voltage	V_F	V	I_{FM}=3.0A	1.1						
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	T_j=25℃	5.0						
			T_j=125℃	100						
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	18						

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	G3AF	G3BF	G3DF	G3GF	G3JF	G3KF	G3MF
Typical Thermal resistance	$R_{\theta J-A}$(1)	℃/W	65						
	$R_{\theta J-L}$(1)		20						
	$R_{\theta J-C}$(1)		15						

Note:
(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
G3AF-G3MF	F1	Approximate 0.034	3000	24000	96000	7” reel
G3AF-G3MF	F2	Approximate 0.034	10000	/	160000	13” reel
G3AF-G3MF	F3	Approximate 0.034	10000	/	120000	13” reel
G3AF-G3MF	F4	Approximate 0.034	7500	/	120000	13” reel

■ Characteristics (Typical)

FIG1：Io-TL Curve




FIG2：Surge Forward Current Capability




FIG3：Typial Forward Voltage






FIG4:Typical Reverse Characteristics




■ Outline Dimensions



SMAF		
Dim	Min	Max
A	2.40	2.80
B	1.35	1.45
C	3.40	3.60
D	4.40	4.80
E	1.05	1.25
F	0.50	1.00
G	0.15	0.25

■ Suggested pad layout



SMAF	
Dim	Millimeters
P1	6.50
P2	4.00
P3	1.50
Q1	2.50
Q2	1.70

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.