

Low VF Bridge Rectifiers





Features

- Glass passivated chip junction
- Low VF
- Thin single in-line package
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package**: 2KBJ
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GBLL408
Device marking code			GBLL408
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	800
Maximum RMS Voltage	V_{RMS}	V	560
Maximum DC blocking Voltage	V_{DC}	V	800
Average Rectified Output Current @60Hz sine wave, R-load, T_a =25℃	I_O	A	4.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	135
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			250
Current squared time @1ms≤t≤8.3ms Tj=25℃,rating of per diode	I^2t	A^2S	62.5
Dielectric strength @ terminals to case, AC 1 minute	Vdis	KV	2
Storage temperature	T_{stg}	℃	-55 ~ +150
Junction temperature	T_j	℃	-55 ~ +150

■Electrical Characteristics（Ta=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	GBLL408
Maximum instantaneous forward voltage drop per diode	V_F	V	I_{FM}=2.0A	0.92
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j =25℃	5
			T_j =125℃	100
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	38

■Thermal Characteristics （Ta=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	GBLL408
Thermal Resistance	Between junction and ambient	RθJ-A	℃/W	47
	Between junction and case	RθJ-C		10

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GBLL408	B1	Approximate 2.19	22	1320	5280	Tube

■ Characteristics(Typical)

FIG1:Io-Ta Curve




FIG2:Surge Forward Current Capability




FIG3: Typical Forward Voltage






FIG4:Typical Reverse Characteristics



■ Outline Dimensions



2KBJ		
Dim	Min	Max
A	19.2	21.2
B	1.2	1.8
C	1.0	1.2
D	Typ：3.0	
E	4.9	5.1
F	10.5	11.5
G	2.0	3.0
H	13.0	15.0
I	3.0	4.0
J	0.9	1.1
K	0.4	0.6

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.