


# Bridge Rectifiers

GBPC-W



GBPC





## Features

- Universal 3-way terminals：snap-on，wire wrap-around，or PCB mounting
- Glass passivated chip junction
- High surge current capability
- Low thermal resistance
- Solder dip 275 °C max. 7 s, per JESD 22-B106

## Typical Applications

General purpose use in AC/DC bridge full wave rectification for power supply, home appliances, office equipment, industrial automation applications.

## Mechanical Data

- **Package**: GBPC、GBPC-W
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Suffix letter “W” added to indicate wire leads(e.g. GBPC3510W).

## ■Maximum Ratings ($T_a$=25℃ Unless otherwise specified）

| PARAMETER | SYMBOL | UNIT | GBPC15005 | GBPC1501 | GBPC1502 | GBPC1504 | GBPC1506 | GBPC1508 | GBPC1510 |
|---|---|---|---|---|---|---|---|---|---|
| Device marking code | | | GBPC15005 | GBPC1501 | GBPC1502 | GBPC1504 | GBPC1506 | GBPC1508 | GBPC1510 |
| Maximum Repetitive Peak Reverse Voltage | $V_{RRM}$ | V | 50 | 100 | 200 | 400 | 600 | 800 | 1000 |
| Maximum RMS Voltage | $V_{RMS}$ | V | 35 | 70 | 140 | 280 | 420 | 560 | 700 |
| Maximum DC blocking Voltage | $V_{DC}$ | V | 50 | 100 | 200 | 400 | 600 | 800 | 1000 |
| Average rectified output current @60Hz sine wave, R-load, $T_C$ =100℃ | $I_O$ | A | 15 | | | | | | |
| Forward Surge Current (Non-repetitive) @8.3ms, Half-sine wave,1 cycle, Tj=25℃ | $I_{FSM}$ | A | 300 | | | | | | |
| Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃ | | | 600 | | | | | | |
| Current squared time @1ms≤t≤8.3ms Tj=25℃, Rating of per diode | $I^2t$ | $A^2S$ | 374 | | | | | | |
| Storage temperature | Tstg | ℃ | -55 ~ +150 | | | | | | |
| Junction temperature | Tj | ℃ | -55 ~ +150 | | | | | | |
| Dielectric strength @ Terminals to case, AC 1 minute | Vdis | KV | 2.5 | | | | | | |
| Mounting torque @Recommend torque：5kg·cm | Tor | kg·cm | 8 | | | | | | |

## ■Electrical Characteristics（$T_a$=25℃ Unless otherwise specified）

| PARAMETER | SYMBOL | UNIT | TEST CONDITIONS | GBPC15005 | GBPC1501 | GBPC1502 | GBPC1504 | GBPC1506 | GBPC1508 | GBPC1510 |
|---|---|---|---|---|---|---|---|---|---|---|
| Maximum instantaneous forward voltage drop per diode | VF | V | $I_{FM}$=7.5A | 1.1 | | | | | | |
| Maximum DC reverse current at rated DC blocking voltage per diode | IR | μA | $T_j$=25℃ | 5 | | | | | | |
| | | | $T_j$=125℃ | 100 | | | | | | |
| Typical junction capacitance | Cj | pF | Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C | 107 | | | | | | |

## ■Thermal Characteristics （$T_a$=25℃ Unless otherwise specified）

| PARAMETER | | SYMBOL | UNIT | GBPC15005 | GBPC1501 | GBPC1502 | GBPC1504 | GBPC1506 | GBPC1508 | GBPC1510 |
|---|---|---|---|---|---|---|---|---|---|---|
| Thermal Resistance | Between junction and case, With heatsink | $R_{\theta J-C}$ | ℃/W | 1.5 | | | | | | |

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

## ■Ordering Information (Example)

| PREFERED P/N | PACKAGE CODE | UNIT WEIGHT (g) | MINIMUM PACKAGE(pcs) | INNER BOX QUANTITY(pcs) | OUTER CARTON QUANTITY(pcs) | DELIVERY MODE |
|---|---|---|---|---|---|---|
| GBPC15005 ~ GBPC1510 | A1 | Approximate 13.8 | 50 | 50 | 500 | Paper Box |
| GBPC15005W ~ GBPC1510W | A1 | Approximate 13 | 50 | 50 | 500 | Paper Box |

## ■ Characteristics (Typical)

FIG1:Io-Tc Curve





FIG2:Surge Forward Current Capability




FIG3: Typical Forward Voltage







FIG4:Typical Reverse Characteristics




## ■ Outline Dimensions




| GBPC-W | | |
|---|---|---|
| **Dim** | **Min** | **Max** |
| A | 28.2 | 28.8 |
| B | 17.1 | 19.1 |
| C | 10.4 | 12.4 |
| D | 0.95 | 1.05 |
| E | 7.6 | 8.2 |
| F | 30 | / |
| G | 4.5 | 5.5 |

| GBPC | | |
|---|---|---|
| **Dim** | **Min** | **Max** |
| A | 28.2 | 28.8 |
| B | 15.3 | 17.3 |
| C | 17.1 | 19.1 |
| D | 13.2 | 15.2 |
| E | 0.75 | 0.85 |
| F | 6.2 | 6.4 |
| G | 2.4 | 2.6 |
| H | 7.6 | 8.2 |
| I | 19 | / |
| J | 4.5 | 5.5 |

# Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.