

Surface Mount Fast Recovery Rectifier





Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.

Mechanical Data

- **P**ackage: DO-214AB (SMC)

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

- Terminals: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- Polarity: Color band denotes the cathode end

■ Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GR5A	GR5B	GR5D	GR5G	GR5J	GR5K	GR5M
Device marking code			GR5A	GR5B	GR5D	GR5G	GR5J	GR5K	GR5M
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	50	100	200	400	600	800	1000
Average Rectified Output Current @60Hz sine wave, Resistance load, TL (FIG.1)	I_O	A	5.0						
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	120						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			200						
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	60						
Storage Temperature	T_{stg}	℃	-55 ~ +150						
Junction Temperature	T_j	℃	-55 ~ +150						

■ Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	GR5A	GR5B	GR5D	GR5G	GR5J	GR5K	GR5M
Maximum instantaneous forward voltage	VF	V	I_{FM}=5.0A	1.3						
Maximum reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A, I_{rr}=0.25A	150				250	500	
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	T_j=25℃	5						
			T_j=125℃	100						
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	57				39	31	

■ Thermal Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	GR5A	GR5B	GR5D	GR5G	GR5J	GR5K	GR5M
Typical Thermal Resistance	RθJ-A(1)	℃/W	48						
	RθJ-L(1)		15						
	RθJ-C(1)		12						

Note (1)
Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.6" x 0.6" (16 mm x 16 mm) copper pad areas

■ Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
GR5A~GR5M	F1	Approximate 0.254	3000	/	42000	13" reel

■ Characteristics (Typical)

FIG.1: Io-TL Curve




FIG.2: Forward Surge Current Capability




FIG.3: Typical Forward Voltage




FIG.4: Typical Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time




■ Outline Dimensions



DO-214AB (SMC)		
Dim	Min	Max
A	6.60	7.11
B	2.85	3.27
C	5.59	6.22
D	7.75	8.13
E	1.99	2.61
F	0.15	0.31
G	0.76	1.52
H	0.05	0.20

■ Suggested pad layout



DO-214AB (SMC)	
Dim	Min
P1	9.9
P2	3.84
Q1	3.03
Q2	3.82

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.