

Bridge Rectifiers





Features

- Glass passivated chip junction
- Ideal for printed circuit boards
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for switching power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package**: KBL
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■ Maximum Ratings (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Device marking code			KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	35	70	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	50	100	200	400	600	800	1000
Average rectified output current @60Hz sine wave, R-load, T_C =120℃	I_O	A	4.0						
Forward Surge Current (Non-repetitive) @8.3ms, Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	120						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			240						
Current Squared Time @1ms≤t≤8.3ms, Tj=25℃,Rating of per diode	I^2t	A^2S	59.8						
Storage temperature	T_{stg}	℃	-55 ~ +150						
Junction temperature	T_j	℃	-55 ~ +150						

■ Electrical Characteristics (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Maximum instantaneous forward voltage drop per diode	VF	V	I_{FM}=2.0A	1.0						
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j =25℃	5						
			T_j =125℃	100						
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	35						

■ Thermal Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	KBL4005	KBL401	KBL402	KBL404	KBL406	KBL408	KBL410
Thermal Resistance	Between junction and ambient	RθJ-A	℃/W	25						
	Between junction and lead	RθJ-L		13						
	Between junction and case	RθJ-C		3.5						

■ Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
KBL4005 ~ KBL410	A1	Approximate 4.54	500	500	4000	Paper Box

■ Characteristics (Typical)

FIG1:Io-Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Typical Forward Voltage






FIG4:Typical Reverse Characteristics



■ Outline Dimensions



KBL		
Dim	**Min**	**Max**
A	13.7	15.7
B	15.2	16.3
C	1.2	1.3
D	16	/
E	4.6	5.6
F	5.5	6.5
G	1.8	2.4
H	18.5	19.5

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.