

Bridge Rectifiers





Features

- Ideal for automated placement
- Glass passivated chip junction
- High surge current capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

General purpose use in AC/DC bridge full wave rectification for power supply, lighting ballast, battery charger, home appliances, office equipment, and telecommunication applications.

Mechanical Data

- **Package**: MBLS
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MBL1S	MBL2S	MBL4S	MBL6S	MBL8S	MBL10S
Device marking code			MBL1S	MBL2S	MBL4S	MBL6S	MBL8S	MBL10S
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	100	200	400	600	800	1000
Maximum RMS Voltage	V_{RMS}	V	70	140	280	420	560	700
Maximum DC blocking Voltage	V_{DC}	V	100	200	400	600	800	1000
Average rectified output current @60Hz sine wave, R-load, Tc=125℃	I_O	A	0.8					
Forward Surge Current (Non-repetitive) @8.3ms Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	30					
Current squared time @1ms≤t<8.3ms Tj=25℃，Rating of per diode	I^2t	A^2s	3.7					
Storage temperature	T_{stg}	℃	-55 ~ +150					
Junction temperature	T_j	℃	-55 ~ +150					

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MBL1S	MBL2S	MBL4S	MBL6S	MBL8S	MBL10S
Maximum instantaneous forward voltage drop per diode	VF	V	I_{FM}=0.4A	1.0					
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j=25℃	5					
			T_j=125℃	50					
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	10					

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	MBL1S	MBL2S	MBL4S	MBL6S	MBL8S	MBL10S
Typical Thermal Resistance	Between junction and ambient	RθJ-A	℃/W	65.0					
	Between junction and lead	RθJ-L		28.0					
	Between junction and case	RθJ-C		18.0					

Note: Device mounted on P.C.B with 35mm*25mm*1.7mm.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MBL1S ~ MBL10S	F1	Approximate 0.083	4000	/	64000	13’ reel
MBL1S ~ MBL10S	F3	Approximate 0.083	5000	/	80000	13’ reel

■ Characteristics (Typical)

FIG1:Io-Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Typical Forward Voltage






FIG4:Typical Reverse Characteristics




■ Outline Dimensions



MBLS		
Dim	Min	Max
A	3.60	4.00
B	6.40	7.00
C	2.20	2.60
D	4.50	4.90
E	1.30	1.50
F	1.40	1.60
G	0.56	0.84
H	0.15	0.35
I	0.20Max	
J	0.70	1.10

■ Suggested pad layout



Dim	Min
P1	6.00
P2	2.40
Q1	1.84
Q2	1.20

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.