
Schottky Diodes



Features

- High frequency operation
- Low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package**: TO-220AB
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity**: As marked

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER		SYMBOL	UNIT	MBR40150CT
Device marking code				MBR40150CT
Repetitive Peak Reverse Voltage		V_{RRM}	V	150
Average Rectified Output Current @60Hz sine wave, R-load, Tc=107℃		I_O	A	40
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, Ta=25℃		I_{FSM}	A	300
Surge(Non-repetitive)Forward Current @1ms, square wave, 1 time, Ta=25℃				600
Current Squared Time @1ms≤t≤8.3ms Tj=25℃,		I^2t	A^2s	373
Typical junction capacitance	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C.	Cj	pF	410
Storage Temperature		T_{stg}	℃	-55 ~ +175
Junction Temperature		Tj	℃	-55 ~ +175

■Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	Min	Typ	Max
Peak Forward Voltage	V_{FM}	V	I_{FM}=20.0A Ta=25℃	0.5	0.815	0.85
			I_{FM}=20.0A Ta=125℃	-	0.68	0.72
Maximum DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	mA	V_{RM}=V_{RRM} Tj=25℃	-	-	0.1
	I_{RRM2}		V_{RM}=V_{RRM} Tj=125℃	-	-	20

Note1:Pulse test:300uS pulse widh,1% duty cycle

Note2:Pulse test:pulse widh 40mS

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	MBR40150CT
Thermal Resistance	Between junction and ambient	$R_{\theta J-A}$	℃/W	50.0
	Between junction and case	$R_{\theta J-C}$	℃/W	2.0

■Characteristics (Typical)

FIG1:Io -Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Forward Voltage




FIG.4: Instantaneous Reverse Characteristics






FIG.5: Maximum Non-Repetitve Peak Forword



■Outline Dimensions



TO-220AB		
Dim	Min	Max
A	9.95	10.35
B	2.55	2.95
C	3.8	4.0
D	14.95	15.25
E	3.75	4.25
F	0.26	0.5
G	0.68	0.94
H	13.4	13.9
I	2.35	2.65
J	4.38	4.78
K	1.14	1.4
L	2.37	2.79

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.