
Schottky Diodes



Features

- High frequency operation
- Low forward voltage drop
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260℃

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package**: TO-263
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity**: As marked

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MBRBL2060CT
Device marking code			MBRBL2060CT
Repetitive Peak Reverse Voltage	V_{RRM}	V	60
Average Rectified Output Current @60Hz sine wave, R-load, T_C=126℃	I_O	A	20
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, T_a=25℃	I_{FSM}	A	150
Current Squared Time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	94
Storage Temperature	Tstg	℃	-55 ~ +150
Junction Temperature	Tj	℃	-55 ~ +150

■Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MBRBL2060CT
Maximum instantaneous forward voltage drop per diode	V_{FM}	V	I_{FM}=10.0A	0.6
Maximum DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	mA	V_{RM}=V_{RRM} T_a=25℃	0.2
	I_{RRM2}		V_{RM}=V_{RRM} T_a=100℃	30

Note1:Pulse test:300uS pulse widh,1% duty cycle

Note2:Pulse test:pulse widh 40mS

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	MBRBL2060CT
Thermal Resistance	Between junction and case	$R_{\theta J-C}$	℃/W	2.0

■Ordering Information (Example)

PREFERED P/N	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MBRBL2060CT	Approximate 1.43	50	2000	8000	Tube
	Approximate 1.43	1000	2000	10000	Reel

■Characteristics (Typical)

FIG1:Io -Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Forward Voltage






FIG.4: Typical Reverse Characteristics




■Outline Dimensions



TO-263		
Dim	Min	Max
A	9.5	11.5
B	9.7	10.5
C	8.4	9.0
D	0.28	0.64
E	0.68	0.94
F	4.55	5.6
G	4.04	5.10
H	1.14	1.4
I	0	0.2
J	4.9	6.05
K	1.79	2.79
L	7.3	7.9
M	6.2	6.8
N	7.6	8.2

■Suggested Pad Layout



Dim	Millimeters
A	12.7
B	9.4
C	16.6
P	5.08
Q1	3.8
Q2	1.35

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.