
Ultra-Fast Recovery Diodes 60A FRED





Features

- High frequency operation
- High surge forward current capability
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Guard ring for enhanced ruggedness and long term reliability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

Typical applications are in switching power supplies, converters, freewheeling diodes, and reverse battery protection.

Mechanical Data

- **Package**: TO-247AC
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity**: As marked

■Maximum Ratings (Tj=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MUR6065P
Device marking code			MUR6065P
Repetitive Peak Reverse Voltage	V_{RRM}	V	650
Average Rectified Output Current @60Hz half sine-wave, R-load, Tc(FIG.1)	I_o	A	60
Surge(Non-repetitive)Forward Current @60Hz half sine-wave, 1 cycle, Tj=25℃	IFSM	A	500
Current Squared Time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s.	1037
Storage Temperature	T_{stg}	℃	-55 ~ +175
Junction Temperature	T_j	℃	-55 ~ +175
Typical Junction capacitance @4V,1MHz	Cj	pF	295

■Electrical Characteristics（Tj=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
instantaneous forward voltage drop per diode	VFM	V	I_{FM}=60.0A Tj=25℃		-	1.9	2.5
DC reverse current at rated DC blocking voltage per diode	I_{RRM1}	uA	VRM=VRRM Tj=25℃		-	-	5.0
	I_{RRM2}		VRM=VRRM Tj=125℃		-	-	200
Reverse Recovery Time	Trr	ns	I_F=0.5A I_{RM}=1A I_{RR}=0.25A Tj=25℃		-	45	75
			Tj=25℃	I_F=30A di/dt=-200A/us V_{RM}=400V	-	80	-
			Tj=125℃		-	132	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	4.7	-
			Tj=125℃		-	13.6	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	190	-
			Tj=125℃		-	900	-

■Thermal Characteristics （Tj=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	MUR6065P
Thermal Resistance	Between junction and case	$R_{\theta J-C}$	℃/W	1.0

■Ordering Information (Example)

PREFERED P/N	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MUR6065P	Approximate 6.0	30	360	1800	Tube

■Characteristics (Typical)

FIG1:Io -Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Forward Voltage




FIG4: Typical Reverse Characteristics






FIG.5 Diagram of circuit and Testing wave form of reverse recovery time



■Outline Dimensions



TO-247AC		
Dim	Min	Max
A	4.80	5.20
A1	2.21	2.61
A2	1.85	2.15
b	1.11	1.36
b2	1.91	2.21
c	0.51	0.75
D	20.70	21.30
D1	16.25	16.85
E	15.50	16.10
E1	13.00	13.60
E2	4.80	5.20
E3	2.30	2.70
e	10.88BSC	
L	19.62	20.22
L1	-	4.30
ϕP	3.40	3.80
ϕP1	-	7.30
S	6.15BSC	

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.