

Surface Mount Super Fast Recovery Rectifier





Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, and telecommunication.

Mechanical Data

- **Package**: DO-214AC(SMA)
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	MURS220A	MURS240A	MURS260A
Device marking code			MURS220A	MURS240A	MURS260A
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	200	400	600
Maximum RMS Voltage	V_{RMS}	V	140	280	420
Maximum DC blocking Voltage	V_{DC}	V	200	400	600
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I_O	A	2.0		
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	50		
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			100		
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	10.375		
Storage temperature	T_{stg}	℃	-55 ~ +150		
Junction temperature	T_j	℃	-55 ~ +150		

■Electrical Characteristics（Ta=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MURS220A	MURS240A	MURS260A
Maximum instantaneous forward voltage	V_F	V	I_{FM}=2.0A	0.92	1.25	
Maximum reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A, I_{rr}=0.25A	25	50	
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	T_j=25℃	5.0		
			T_j=125℃	50		
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	25	25	24

■Dynamic Characteristics

◆ MURS220A

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	26	-
			Tj=25℃	I_F=2A di/dt=-200A/us V_{RM}=100V	-	23	-
			Tj=125℃		-	30	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	3.1	-
			Tj=125℃		-	5.0	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	35.4	-
			Tj=125℃		-	73.8	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25℃	I_R=1.8 A，L=15 mH	24.3	-	-

◆ MURS240A

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	35	-
			Tj=25℃	I_F=2A di/dt=-200A/us V_{RM}=200V	-	30	-
			Tj=125℃		-	45	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	3.7	-
			Tj=125℃		-	5.8	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	55.4	-
			Tj=125℃		-	130.6	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25℃	I_R=0.5A，L=15 mH	1.9	-	-

◆ MURS260A

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	50	-
			Tj=25℃	I_F=2A di/dt=-200A/us V_{RM}=400V	-	43	-
			Tj=125℃		-	66	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	5.0	-
			Tj=125℃		-	7.4	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	105.9	-
			Tj=125℃		-	243.8	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25℃	I_R=0.5A，L=15 mH	1.9	-	-

■Thermal Characteristics （Ta=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	MURS220A	MURS240A	MURS260A
Typical Thermal resistance	$R_{\theta J-A}$(1)	℃/W	65		
	$R_{\theta J-L}$(1)		25		
	$R_{\theta J-C}$(1)		20		

Note:

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

■ Characteristics (Typical)

FIG.1: Io-TL Curve




FIG.2: Forward Surge Current Capadility




FIG.3: Typical Forward Voltage




FIG.4: Typical Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■Ordering Information (Example)


PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MURS220A-MURS260A	F1	Approximate 0.059	5000	/	80000	13” reel
MURS220A-MURS260A	F2	Approximate 0.059	7500	/	120000	13” reel
MURS220A-MURS260A	F3	Approximate 0.059	7500	/	60000	13” reel
MURS220A-MURS260A	F4	Approximate 0.059	1800	14400	57600	7” reel
MURS220A-MURS260A	F5	Approximate 0.059	2000	16000	64000	7” reel
MURS220A-MURS260A	F6	Approximate 0.059	5000	/	100000	13” reel

■ Outline Dimensions



DO-214AC(SMA)		
Dim	Min	Max
A	1.25	1.58
B	2.40	2.83
C	4.00	4.75
D	1.90	2.30
E	4.93	5.28
F	0.76	1.41
G	0.05	0.20
H	0.15	0.31
I	1.70	2.10

■Suggested Pad Layout



DO-214AC(SMA)	
Dim	Millimeters
P1	4.00
P2	1.50
P3	6.50
Q1	2.50
Q2	1.70

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.