

Surface Mount Ultrafast Rectifier Diode





Features

- Ultrafast reverse recovery time
- Low leakage current
- Low switching losses, high efficiency
- High forward surge capability
- Solder dip 260 °C max. 10 s, per JESD 22-B106

Typical Applications

For use in high frequency rectification and freewheeling application in switching mode converters and inverters for consumer, computer and telecommunication.

Mechanical Data

- **Package**: DO-214AB (SMC)

Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free

- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity**: Color band denotes the cathode end

■Maximum Ratings (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	MURS480
Device marking code			MURS480
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	800
Maximum RMS Voltage	V_{RMS}	V	560
Maximum DC blocking Voltage	V_{DC}	V	800
Average Rectified Output Current @60Hz sine wave, Resistance load, TL (FIG.1)	I_O	A	4.0
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	100
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			200
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	41.5
Storage Temperature	T_{stg}	℃	-55 ~ +150
Junction Temperature	Tj	℃	-55 ~ +150

■Electrical Characteristics (Ta=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	MURS480
Maximum instantaneous forward voltage	V_F	V	I_{FM}=4.0A	1.85
Maximum reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A, I_{rr}=0.25A	75
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	Tj =25℃	5
			Tj =125℃	50
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	48

■Dynamic Characteristics

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	51	-
			Tj=25℃	I_F=4A di/dt=-200A/us V_{RM}=400V	-	64	-
			Tj=125℃		-	114	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	7.4	-
			Tj=125℃		-	11.2	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	235.8	-
			Tj=125℃		-	635.8	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25℃	I_R=2.8A，L=15 mH	58.8	-	-

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	MURS480
Typical Thermal resistance	$R_{\theta J\text{-}A}$(1)	℃/W	55
	$R_{\theta J\text{-}L}$(1)		15
	$R_{\theta J\text{-}C}$(1)		10

Note(1)
Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.6" x 0.6" (16 mm x 16 mm) copper pad areas

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
MURS480	F1	Approximate 0.248	3000	/	42000	13” reel

■ Characteristics(Typical)

FIG.1: Io-TL Curve




FIG.2: Forward Surge Current Capadility




FIG.3: Typical Forward Voltage




FIG.4: Typical Reverse Characteristics







FIG.5: Diagram of circuit and Testing wave form of reverse recovery time






■ Outline Dimensions



DO-214AB (SMC)		
Dim	Min	Max
A	6.60	7.11
B	2.85	3.27
C	5.59	6.22
D	7.75	8.13
E	1.99	2.61
F	0.15	0.31
G	0.76	1.52
H	0.05	0.20

■ Suggested pad layout



DO-214AB (SMC)	
Dim	Min
P1	9.9
P2	3.84
Q1	3.03
Q2	3.82

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.