
Bridge Rectifiers



Features

- Universal 3-way terminals：snap-on，wire wrap-around，or PCB mounting
- Glass passivated chip junction
- High surge current capability
- Low thermal resistance
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for power supply, home appliances, office equipment, industrial automation applications.

Mechanical Data

- **Package**: S25VB
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102

■Maximum Ratings (T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	S25VB10	S25VB20	S25VB40	S25VB60	S25VB80	S25VB100	S25VB120
Device marking code			S25VB10	S25VB20	S25VB40	S25VB60	S25VB80	S25VB100	S25VB120
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	100	200	400	600	800	1000	1200
Maximum RMS Voltage	V_{RMS}	V	70	140	280	420	560	700	840
Maximum DC blocking Voltage	V_{DC}	V	100	200	400	600	800	1000	1200
Average rectified output current @60Hz sine wave, R-load, T_C =100℃	I_O	A	25						
Forward Surge Current (Non-repetitive) @8.3ms, Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	400						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			800						
Current squared time @1ms≤t≤8.3ms Tj=25℃, Rating of per diode	I^2t	A^2S	664						
Storage temperature	T_{stg}	℃	-55 ~ +150						
Junction temperature	Tj	℃	-55 ~ +150						
Dielectric strength @ Terminals to case, AC 1 minute	V_{dis}	KV	2.5						
Mounting torque @Recommend torque：5kg·cm	Tor	kg·cm	8						

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	S25VB10	S25VB20	S25VB40	S25VB60	S25VB80	S25VB100	S25VB120
Maximum instantaneous forward voltage drop per diode	VF	V	I_{FM}=12.5A	1.0						
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j =25℃	5						
			T_j =125℃	100						
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	145						

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	S25VB10	S25VB20	S25VB40	S25VB60	S25VB80	S25VB100	S25VB120
Thermal Resistance	Between junction and case, With heatsink	$R_{\theta J-C}$	℃/W	1.5						

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

■Ordering Information (Example)

PREFERED P/N	PACKAGE CODE	UNIT WEIGHT (g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S25VB10 ~ S25VB120	A1	Approximate 20	50	50	500	Paper Box

■ Characteristics (Typical)

FIG1:Io-Tc Curve








FIG2:Surge Forward Current Capability







■ Outline Dimensions



S25VB		
Dim	**Min**	**Max**
A	31.1	32.1
B	31.1	32.1
C	17.6	18.6
D	13.7	14.7
E	15.8	16.8
F	15.8	16.8
G	0.75	0.85
H	9.5	10.5
I	/	25
J	6.2	6.4
K	4.5	5.5

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.