
Three Phase Bridge Rectifiers



Features

- Low thermal resistance
- Glass passivated chip junction
- High surge current capability
- Solder dip 275 °C max. 7 s, per JESD 22-B106

Typical Applications

General purpose use in AC/DC bridge full wave rectification for Server、Frequency converter、Industrial power supply.

Mechanical Data

- **Package**: SKBPC
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** As marked on body

■Maximum Ratings (T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	SKBPC2504	SKBPC2506	SKBPC2508	SKBPC2510	SKBPC2512	SKBPC2514	SKBPC2516
Device marking code			SKBPC2504	SKBPC2506	SKBPC2508	SKBPC2510	SKBPC2512	SKBPC2514	SKBPC2516
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	400	600	800	1000	1200	1400	1600
Maximum RMS Voltage	V_{RMS}	V	280	420	560	700	840	980	1120
Maximum DC blocking Voltage	V_{DC}	V	400	600	800	1000	1200	1400	1600
Average rectified output current @60Hz sine wave, R-load With heatsink Tc =110℃	IO	A	25						
Forward Surge Current (Non-repetitive) @8.3ms Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	360						
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			720						
Current squared time @1ms≤t≤8.3ms Tj=25℃, Rating of per diode	I^2t	A^2s	538						
Storage temperature	T_{stg}	℃	-55 ~ +150						
Junction temperature	T_j	℃	-55 ~ +150						
Dielectric strength @ Terminals to case, AC 1 minute	Vdis	KV	2.5						
Mounting torque @Recommend torque：5kg·cm	Tor	kg· cm	8						

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	SKBPC2504	SKBPC2506	SKBPC2508	SKBPC2510	SKBPC2512	SKBPC2514	SKBPC2516
Maximum instantaneous forward voltage drop per diode	V_F	V	I_{FM}=12.5A	1.1						
Maximum DC reverse current at rated DC blocking voltage per diode	I_R	μA	T_j=25℃	5						
			T_j=125℃	500						
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	175					145	

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER		SYMBOL	UNIT	SKBPC2504	SKBPC2506	SKBPC2508	SKBPC2510	SKBPC2512	SKBPC2514	SKBPC2516
Typical Thermal Resistance	Between junction and case, With heatsink	$R_{\theta J-C}$	℃/W	1.5						

Note: Device mounted on 75mm x 45mm x 5.5mm Aluminum Plate Heatsink.

■Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SKBPC2504 ~ SKBPC2516	A1	Approximate 19	50	50	500	Paper Box

■ Characteristics (Typical)

FIG1:Io-Tc Curve




FIG2:Surge Forward Current Capability




FIG3: Typical Forward Voltage






FIG4:Typical Reverse Characteristics



■ Outline Dimensions



SKBPC		
Dim	**Min**	**Max**
A	23.1	24.1
B	23.1	24.1
C	28.2	28.8
D	16.0	17.0
E	/	25
F	10.8	11.2
G	6.2	6.4
H	0.75	0.85
I	4.5	5.5

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise. Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.