

Surface Mount Ultra Fast Recovery Rectifier





Features

- Low profile package
- Ideal for automated placement
- Guardring for overvoltage protection
- Low power losses, high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C

Typical Applications

For use in low voltage high frequency inverters, freewheeling, DC/DC converters, and polarity protection applications.

Mechanical Date

- **Package:** SOD-123HE
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	U1AE	U1BE	U1CE	U1DE	U1FE	U1GE	U1HE	U1JE
Device marking code			U1AE	U1BE	U1CE	U1DE	U1FE	U1GE	U1HE	U1JE
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	150	200	300	400	500	600
Maximum RMS Voltage	V_{RMS}	V	35	70	105	140	210	280	350	420
Maximum DC blocking Voltage	V_{DC}	V	50	100	150	200	300	400	500	600
Average rectified output current @60Hz sine wave, Resistance load, TL (FIG.1)	IO	A	1.0							
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	30							
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			60							
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	3.735							
Storage temperature	T_{stg}	℃	-55 ~ +150							
Junction temperature	T_j	℃	-55 ~ +150							

■Electrical Characteristics (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	U1AE	U1BE	U1CE	U1DE	U1FE	U1GE	U1HE	U1JE
Maximum instantaneous forward voltage	V_F	V	I_{FM}=1.0A	0.92				1.25		1.7	
Maximum reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A, I_{rr}=0.25A	25						35	
Maximum DC reverse current at rated DC blocking voltage	I_R	μA	Tj =25℃	5							
			Tj =125℃	50							
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	17				15		16	

■Dynamic Characteristics

◆ U1AE THRU U1DE

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	27	-
			Tj=25℃	I_F=1A di/dt=-200A/us V_{RM}=100V	-	18	-
			Tj=125℃		-	24	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	2.4	-
			Tj=125℃		-	3.9	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	21.6	-
			Tj=125℃		-	46.6	-

◆ U1FE THRU U1GE

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	26	-
			Tj=25℃	I_F=1A di/dt=-200A/us V_{RM}=200V	-	22	-
			Tj=125℃		-	31	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	1.9	-
			Tj=125℃		-	3.5	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	21.1	-
			Tj=125℃		-	54.9	-

◆ U1HE THRU U1JE

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	38	-
			Tj=25℃	I_F=1A di/dt=-200A/us V_{RM}=400V	-	32	-
			Tj=125℃		-	52	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	2.9	-
			Tj=125℃		-	4.7	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	45.8	-
			Tj=125℃		-	121.9	-

■Thermal Characteristics (T_a=25℃ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	U1AE	U1BE	U1CE	U1DE	U1FE	U1GE	U1HE	U1JE
Typical Thermal resistance	$R_{\theta J-A}$(1)	℃/W	65							
	$R_{\theta J-L}$(1)		25							
	$R_{\theta J-C}$(1)		20							

Note:
(1)Thermal resistance between junction and ambient and between junction and lead mounted on P.C.B with 3mm*3mm copper pad areas.

■ Characteristics (Typical)

FIG.1: Io-TL Cure




FIG.2: Forward Surge Current Capability




FIG.3: Typical Forward Characteristics






FIG.4: Typical Reverse Characteristics




■ Outline Dimensions



SOD-123HE		
Dim	Min	Max
A	1.88	2.18
B	3.70	4.00
C	3.19	3.61
D	1.05	1.35
E	0.61	0.91
F	2.20	2.90
G	0.40	0.80
H	0.30 TYP	
I	0.10	0.30
J	0.85	1.15
K	0.00	0.30
L	0.15	0.45

■ Suggested pad layout



SOD-123HE	
Dim	Millimeters
P1	0.64
Q1	2.54
Q2	2.67
Q3	1.27
Q4	0.76

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.