
Surface Mount Super Fast Recovery Rectifier




Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260°C

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer and telecommunication.



Mechanical Data

- **Package**: DO-214AA (SMB)
  Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals**: Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■Maximum Ratings (T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	UG2A	UG2B	UG2C	UG2D	UG2F	UG2G	UG2H	UG2J
Device marking code			UG2A	UG2B	UG2C	UG2D	UG2F	UG2G	UG2H	UG2J
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	V	50	100	150	200	300	400	500	600
Maximum RMS Voltage	V_{RMS}	V	35	70	105	140	210	280	350	420
Maximum DC blocking Voltage	V_{DC}	V	50	100	150	200	300	400	500	600
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I_O	A	2.0							
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave,1 cycle, Tj=25℃	I_{FSM}	A	50							
Forward Surge Current (Non-repetitive) @1ms, square wave, 1 cycle, Tj=25℃			100							
Current squared time @1ms≤t≤8.3ms Tj=25℃	I^2t	A^2s	10.375							
Storage temperature	T_{stg}	℃	-55 ~ +150							
Junction temperature	T_j	℃	-55 ~ +150							

■Electrical Characteristics（T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	UG2A	UG2B	UG2C	UG2D	UG2F	UG2G	UG2H	UG2J
Maximum instantaneous forward voltage	V_F	V	I_{FM}=2.0A	0.92				1.25		1.7	
Maximum reverse recovery time	t_{rr}	ns	I_F=0.5A,I_R=1.0A, I_{rr}=0.25A	25						35	
Maximum DC reverse current at rated DC blocking voltage	IR	μA	Tj =25℃	5.0							
			Tj =125℃	50							
Typical junction capacitance	Cj	pF	Measured at 1MHz and Applied Reverse Voltage of 4.0 V.D.C	40				26		23	

■Dynamic Characteristics

◆ UG2A THRU UG2D

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	26	-
			Tj=25℃	I_F=2A di/dt=-200A/us V_{RM}=100V	-	23	-
			Tj=125℃		-	30	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	3.1	-
			Tj=125℃		-	5.0	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	35.4	-
			Tj=125℃		-	73.8	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25℃	I_R=1.8 A，L=15 mH	24.3	-	-

◆ UG2F THRU UG2G

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	26	-
			Tj=25℃	I_F=2A di/dt=-200A/us V_{RM}=200V	-	24	-
			Tj=125℃		-	36	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	2.7	-
			Tj=125℃		-	4.5	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	32.3	-
			Tj=125℃		-	82.8	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25℃	I_R=0.5A，L=15 mH	1.9	-	-

◆ UG2H THRU UG2J

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		Min	Typ	Max
Reverse Recovery Time	T_{RR}	ns	Tj=25℃	I_F=1A，di/dt=-50A/us V_{RM}=30V	-	40	-
			Tj=25℃	I_F=2A di/dt=-200A/us V_{RM}=400V	-	38	-
			Tj=125℃		-	59	-
Peak recovery current	I_{RRM}	A	Tj=25℃		-	4.2	-
			Tj=125℃		-	6.5	-
Reverse recovery charge	Qrr	nC	Tj=25℃		-	78.9	-
			Tj=125℃		-	192.7	-
Non-repetitive avalanche energy	E_{AS}	mJ	Tj=25℃	I_R=0.7A，L=15 mH	3.7	-	-

■Thermal Characteristics （T_a=25℃ Unless otherwise specified）

PARAMETER	SYMBOL	UNIT	UG2A	UG2B	UG2C	UG2D	UG2F	UG2G	UG2H	UG2J
Typical Thermal resistance	$R_{\theta J-A}$(1)	℃/W	70							
	$R_{\theta J-L}$(1)		20							
	$R_{\theta J-C}$(1)		15							

Note:
(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3" x 0.3" (8.0 mm x8.0 mm) copper pad areas

■ Characteristics (Typical)

FIG.1: Io-TL Curve




FIG2:Surge Forward Current Capability




FIG.3: Typilcal Forward Characteristics




FIG4:Typical Reverse Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
UG2A-UG2J	F1	Approximate 0.096	3000	/	48000	13” reel
UG2A-UG2J	F2	Approximate 0.096	750	6000	24000	7” reel
UG2A-UG2J	F3	Approximate 0.096	500	4000	16000	7” reel

■ Outline Dimensions



DO-214AA(SMB)		
Dim	Min	Max
A	1.85	2.15
B	3.30	3.94
C	4.05	4.75
D	1.99	2.61
E	5.21	5.59
F	0.90	1.41
G	0.05	0.20
H	0.15	0.31

■ Suggested pad layout



DO-214AA(SMB)	
Dim	Millimeters
P1	6.8
P2	4.3
P3	1.8
Q1	2.5
Q2	2.3

Notice

All products, product specifications and data are subject to change without notice to improve reliability, function or design or otherwise.
Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in STARSEA's terms and conditions of sale for such products, STARSEA assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of STARSEA products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.